PA SPECS MAIN HALL
(capacity 1200)

Max. soundlevel @ FOH **103 dB A Leq over 15 minutes**

Effenaar subscribes the National Hearing Convenant which includes a sound limit of 103 dB(A) @ F.O.H., measured Leq over 15 minutes. Effenaar measures with a calibrated Metrao system and microphone. The Effenaar measurements are leading at any time!!!

Stage

– permanent	8 x 7 x 1,2 m
– sidestages	4,5 x 7 x 1,2 m (L+R)

Monitor desk and monitor amplifiers are postioned stage right.
Main PA inputs are positioned at front of house.

Clearance (stage) 8,0 m

Power (sound) 3 x 3 fase 32 A (CEE-form, 5P)

Number	Discription	Type	Brand
16	L/R-LINE ARRAY	E12	Adamson
6	SUB	E219	Adamson
2	FRONTFILL	M12A	Adamson
2	OUTFILL	M12A	Adamson
9	FLOORMONITORS	M212	Adamson
2	SIDEFILL	SX18 + A218	Adamson
2	DRUMFILL	M212 + S119I	Adamson
2	PROCESSING	LM44	Lake
1	FOH. MIXINGDESK DIGITAL 48 CHNL 32 PROGRAMMABLE AUX	VI600	Soundcraft
1	MON. MIXINGDESK DIGITAL 48 CHNL 32 PROGRAMMABLE AUX	VI400	Soundcraft
6	CAT-6A LINES FROM STAGE TO F.O.H.	RJ45	Neutrik
2	OPTICALCON DUO NO SHORT LEADS AVAILABLE!	Fibre	Neutrik
2	BNC	RG59	Neutrik

Extended Microphone set, list at request

4	SHURE WIRELESS UR4S + UR4D RECEIVERS		

EFFENAAR